

IM 7000/ IM 8000/ IM 9000

MAIN SPECIFICATIONS

	IM 7000	IM 8000	IM 9000
GENERAL			
Configuration	Console		
Printing process	Dry, two component & electro-photographic		
Warm-up time	20 seconds	20 seconds	60 seconds
First copy speed: BW	3.2 seconds	3.2 seconds	2.9 seconds
Continuous output speed	70 ppm	80 ppm	90 ppm
Memory: standard	2 GB		
Memory: maximum	2 GB		
HDD: standard	320 GB		
HDD: maximum	320 GB		
Weight	200 kg		
Dimensions: W x D x H	690 x 883 x 1,161 mm		
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz

COPIER			
Multiple copying	Up to 9,999 copies		
Resolution	600 x 600 dpi		
Zoom	From 25% to 400% in 1% steps		

PRINTER			
CPU	Intel® Apollo Lake Processor 1.6 GHz		
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)		
Printer language: option	Genuine Adobe® PostScript®3™, IPDS, PDF Direct from Adobe®		
Print resolution	Maximum (1,200 x 1,200 dpi)		
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host Type A, USB Device IF Type B, Bluetooth, Wireless LAN (IEEE 802.11 b/g/n), USB Host I/F, SD slot, NFC tag, USB Device (TypeB:1Port)		
Network interface: option	Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), RJ45 I/F (Only Copy connect), Ethernet Print only RJ-45 network port		
Network protocol	TCP/IP		
Windows® environments	Windows® Server 2008R2, Windows® 7/8.1/10, Windows® Server 2008/2012/2012R2/2016, Windows® Server 2019		
Mac OS environments	Macintosh OS X v10.12 or later		
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX, XenDesktop, Citrix XenApp		
SAP® environments	SAP® R/3®, SAP® S/4®		

SCANNER			
Scanning: B/W	120 ipm (simplex)/240 ipm (duplex)		
Scanning: full colour	120 ipm (simplex)/240 ipm (duplex)		
Resolution: maximum	1,200x1,200 dpi		
Bundled drivers	Network TWAIN		
Compression method	BW: TIFF (MH, MR, MMR, JBIG2), Grayscale - Colour: JPEG		
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A		
Scan modes	E-mail, Folder, USB, SD Card, URL, FTP, SMB		

FAX			
Circuit	PSTN, PBX		
Compatibility	ITU-T (CCITT) G3		
Transmission speed	G3: approximately 2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission) G3: approximately 3 seconds (200 x 100 dpi, MMR, ITUT #1 chart TTI off, memory transmission)		
Modem speed: maximum	Kbps		
Resolution	Standard mode: 8 x 3.85 line/mm, 200 x 100 dpi, Detail mode: 8 x 7.7 line/mm, 200 x 200 dpi, Super fine mode: 8 x 15.4 line/mm, 16 x 15.4 line/mm, 400 x 400 dpi (with optional SAF memory)		
Compression method	MH, MR, MMR, JBIG		
Page memory size	Standard: 8 MB, With optional SAF memory: 16 MB		
SAF memory size	Standard: 4 MB (approximately 320 pages), Optional: 60 MB (approximately 4,800 pages)		
Memory backup	1 hour(s)		

PAPER HANDLING			
Recommended paper size	A3, A4, A5, A6, B4, B5, B6		
Paper input: standard	4,300 sheets		
Paper input: bypass (standard)	100 sheets		
Paper input: maximum	8,700 sheets		
Paper output: standard	500 sheets		
Paper output: max	3,500 sheets		
Paper weight: standard	Trays : 52 - 256 g/m² Bypass : 52 - 300 g/m² Duplex : 64 - 256 g/m²		

ECOLOGY			
Power consumption: max.	< 1,900 W	< 1,900 W	< 2,100 W
Power consumption: sleep		0.6 W	
TEC*	1.326 kWh/week	1.696 kWh/week	2.507 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

3,000-sheet finisher, 3,000-sheet finisher with 100-sheet stapler, 2,000-sheet Booklet finisher, A3 tray, A4 LCT, LG/B4 tray, Cover interposer, Copy tray, 9-bin mailbox, Output jogger unit, Tab sheet holder, Multi-folding units, Punch units, GBC Streampunch Ultra, Shift sort tray



COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers.

Copyright © 2026 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.